

Volcalis

mineral insulation



COMFORT

Mineral Wool in Roll



Compact slab, supplied in roll, available in 400 and 600 mm wide, for application in dry construction systems.

Applications

Volcalis **COMFORT** is an excellent thermal and acoustic insulation for application in all types of buildings.

Suitable for use in construction and rehabilitation works, such as: partitions, wall lining and ceilings.



Partitions



Wall lining



Ceilings

Benefits

- Good thermal behavior, contributes to the comfort of buildings and reduces energy consumption.
- Due to its internal structure, it is an excellent acoustic insulation.
- Fire resistant, not combustible or conductive to heat.
- Results from a sustainable process that uses raw materials and advanced technologies of high efficiency. It's a 100% recyclable product.
- Easy to apply and to handle.



thermal insulation



acoustic insulation



non-combustible



all around application



sustainable process



comfortable application

Volcalis

mineral insulation



DOC 04.01-004/REV07
startupdesign.pt

COMFORT Roll



Dimensions

Thickness (mm)	50		60		70		90		100	
Width (mm)	400	600	400	600	400	600	400	600	400	600
Length (mm)	2x 6 600		11 000		9 500		7 400		6 600	

Logistics

Un. Packing	6	4	3	2	3	2	3	2	3	2
m ² Packing	15,84		13,20		11,40		8,88		7,92	
Packing by Pallet	24		24		24		24		24	
m ² Pallet	380,16		316,80		273,60		213,12		190,08	

Technical Data

Thermal Resistance (m ² .K/W)	1,35	1,60	1,85	2,40	2,70
Thermal Conductivity (W/m.K)	0,037				
Reaction to Fire	A1				
Thickness Tolerance	T2				
Air Flow Resistivity (kPa.s/m ²)	≥ 5				
Water Vapor Resistance Diffusion Factor (μ)	1				
Designation Code	MW-EN13162-T2-MU1-AW0,85-AFr5 (50 mm) MW-EN13162-T2-MU1-AW1-AFr5 (≥ 60 mm)				

Sound absorption (EN ISO 11654)

Weighted coefficient (α _w)	0,85	1
Absorption class	B	A

Ensaios Itecons, EN ISO 354, ACL 150/24 COMFORT 50 mm, ACL 199/24 COMFORT 60 mm

Transportation and Storage

It is not a dangerous product and therefore does not require special transport precautions. Store in a dry place, protected from moisture and sun. Do not store outside of the original packaging. The packagings are coated with thermo-retractable polyethylene film and later packed with a Multipack system.

Installation

Easy to handle product. After opening the packaging, wait about 5 minutes for the product to recover to the desired thickness. During installation, wear long-sleeved clothing and gloves. If work is done above eye level, wear a mask and goggles.

Certificates



Designed and manufactured in Portugal

Additional information available at www.volcalis.pt

Bustos, Portugal · T (+351) 234 751 533 · geral@volcalis.pt · www.volcalis.pt

